DS039



MADE in ITALY



DS039

I ***DS039*** sono apparecchi di illuminazione per esterni IP65 con design moderno. Nascono da uno studio delle forme semplici e funzionali, ma anche con un effetto magico e poetico. La tendenza attuale è quella di considerare gli spazi esterni una parte molto importante degli edifici. Con l'illuminazione giusta si possono creare luoghi invitanti in cui trascorrere ore piacevoli in completo relax.

DS039 are luminaires for outdoor use IP65 with modern design. They arise from a study of the forms simple and functional forms , but also with magical and poetic effect. The current trend is to consider the outdoor spaces a very important part of the buildings. With the correct lighting, you can create inviting places to spend pleasant hours in complete relaxation.

Struttura: Body:	Realizzata in pressofusione di alluminio a basso contenuto di rame. Injected Alu with low content of copper.
Alimentazione e IP: Input power and IP:	230Vdc, IP65; 230Vdc, IP65;
Colore luce disponibili	Bianco 5000K (a scelta: 3000, 4000 o 6000K) White 5000K (choice: 3000, 4000 or 6000K) oppure Rosso, Verde, Blu e RGB
Durata ed efficienza LED: Lifetime and efficiency:	60000h 166lm/W (led CREE oppure NICHIA); 60000h 166lm/W (Led CREE or NICHIA);
Resistenza agli urti Impact resistance:	IK08; IK08;


Norme di riferimento: EN 60598-1, EN62471, EN55015, EN61547, EN61000-3-2, EN61000-3-3, UNI EN 12464-1.
Direttive: 2011/65/CE, 2006/95/CE, 2004/108/CE.
Reference standards: EN 60598-1, EN62471, EN55015, EN61547, EN61000-3-2, EN61000-3-3, UNI EN 12464-1
Guidelines: 2011/65/CE, 2006/95/CE, 2004/108/CE.

IP66 RoHS IK08


DS039_03



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




4W, 2 led, 640lm (equiv. Alogeno 30W), Apert. Fascio 45°, 220vac

4W, 2 led 640lm (equiv. Halogen 30W), 30° Beam angle, 220Vac


DS039_03Q



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




4W, 2 led, 664lm (equiv. Alogeno 30W), Apert. Fascio 45°, 220vac

4W, 2 led 664lm (equiv. Halogen 30W), 30° Beam angle, 220Vac


DS039_09



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




9W, 3led, 1494lm (eq. alog. 100W), Aper. fascio 45°, 220vac

9W, 3led 1494lm (equiv. Halogen 100W), Beam angle 45°, 220Vac


DS039_09Q



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




9W, 3led, 1494lm (eq. alog. 100W), Aper. fascio 45°, 220vac

9W, 3led 1494lm (equiv. Halogen 100W), Beam angle 45°, 220Vac


DS039_ONE



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




4W, 2 led, 664lm (equiv. Alogeno 30W), Aper. fascio 180°, 220vac

4W, 2 led 664lm (equiv. Halogen 30W), Beam angle 180°, 220Vac


DS039_18



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




20W, 6led, 3320lm (eq. alog. 200w), Aper. fascio 45°, 220vac

20W, 6led 3320lm (equiv. Halogen 200w), 45° Beam angle, 220Vac


DS039_18Q



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




20W, 6led, 3320lm (eq. alog. 200W), Aper. fascio 45°, 220vac

20W, 6led 3320lm (equiv. Halogen 200W), 45° Beam angle, 220Vac


DS039_30



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




30W, 9led, 4980lm (eq. alog. 300W), Aper. fascio 45°, 220vac

30W 9led 4980lm (equiv. Halogen 300W), Beam angle 45°, 220Vac


DS039_30Q



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




30W, 9led, 4980lm (eq. alog. 300W), Aper. fascio 45°, 220vac

30W, 9led 4980lm (equiv. Halogen 300W), Beam angle 45°, 220Vac


DS039_ A3



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




6W, 2 led, 780lm (equiv. Alogeno 50W), Apert. Fascio 7° su due lati

6W, 2 led 780lm (equiv. Halogen 50W), Beam angle 7° on two sides


DS039_ B3



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




12W, 4 led, 1560lm (equiv. Alogeno 100W), Apert. Fascio 7° su 4 lati

12W 4 led 1560lm (equiv. Halogen 100W), Beam angle 7° on 4 sides


DS039_01



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




9W, 4 led, 1350lm (eq. alog. 100W), Apert. fascio 45°, 60° o 120° su 1 lato

9W 4 led 1350lm (eq. halogen 100W), Beam angle 45°, 60° or 120° on one side


DS039_01-2



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




9*2W, 8led, 2700lm (eq. alog. 200W), Aper. fascio 45°, 60° o 120° su 2 lato

*9*2W, 8 led 2700lm (equiv. Halogen 200W), Beam angle 45°, 60° or 120° on two sides*


DS039_101



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*




12W, 4led, 1920lm (equiv. Alogeno 150W), Apert. Fascio 7° su 1 lato

12W , 4led 1920lm (equiv. Halogen 150W), Beam angle 7° on one sides


DS039_101-2



FOTOMETRICA - *PHOTOMETRIC*



DIMENSIONE - *DIMENSION*



12*2W, 8 led, 3840lm (equiv. Alogeno 300W), Apert. Fascio 7° su 2 lati

*12*2W 8led 3840lm (equiv. Halogen 300W), Beam angle 7° on two sides*